

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
15 January 2004 (15.01.2004)

PCT


(10) International Publication Number
WO 2004/006179 A1

- (51) International Patent Classification⁷: **G06K 19/08**
- (21) International Application Number:
PCT/IB2003/003146
- (22) International Filing Date: **7 July 2003 (07.07.2003)**
- (25) Filing Language: **English**
- (26) Publication Language: **English**
- (30) Priority Data:
02291732.2 **9 July 2002 (09.07.2002)** **EP**
- (71) Applicant (for all designated States except US):
SCHLUMBERGER SYSTEMES [FR/FR]; 50 avenue Jean-Jaurès, F-Montrouge 92120 (FR).
- (71) Applicant (for MC only): **SCHLUMBERGER MALCO, INC. [US/US]; 9800 Reistertown road, Owings Mills, MD 21117 (US).**

- (72) Inventors; and
(75) Inventors/Applicants (for US only): **LEIBENGUTH, Joseph [FR/FR]; 72 rue Royale, F-92210 Saint-Cloud (FR). EL YAMANI, Hayat [FR/FR]; 10 rue Allée Bellevue, F-94230 Cachan (FR). PONSAN, Véronique [FR/FR]; 94 rue de la Charpenterie, F-45000 Orléans (FR). PERBEN, Cédric [FR/FR]; 144 montée des Roches, F-69760 Limonest (FR).**
- (74) Common Representative: **SCHLUMBERGER SYSTEMES; C/O Vincent YQUEL, 50 avenue Jean-Jaurès, F-Montrouge 92120 (FR).**
- (81) Designated States (national): **AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD,**

[Continued on next page]

(54) Title: **REMOVABLY CONNECTED DATA CARRIERS MADE OF DIFFERENT MATERIALS AND READABLE BY RESPECTIVE DIFFERENT READER TYPES**



(57) Abstract: A system comprises a first data carrier (MOD) and a second data carrier (CDC). The first data carrier (MOD) is inserted in the second data carrier (CDC). The system is characterized in that, the first data carrier (MOD) is removable from the second data carrier (CDC), in that the first data carrier (MOD) is readable by a first reading machine, and in that the second data carrier (CDC) is readable by a second reading machine, which is different than the first reading machine.

WO 2004/006179 A1

REMOVABLY CONNECTED DATA CARRIERS MADE OF DIFFERENT MATERIALS AND READABLE BY
RESPECTIVE DIFFERENT READER TYPES

FIELD OF THE INVENTION

5 The invention concerns a system comprising a first data carrier and a second data carrier. The first data carrier is inserted in the second data carrier. The first data carrier may be, for example, a GSM plug. The second data carrier may be, for example, an optical data
10 carrier.

BACKGROUND OF THE INVENTION

 A prior art method of manufacturing a data
15 carrier in the ISO format made of polycarbonate comprises the following steps.

 In a moulding step a CD made of polycarbonate is moulded. The CD is 1.2 mm thick to meet the CD standards requirements. In a depositing step a round shaped
20 metallic layer is deposited on the CD to define an optical data storage area. In a cutting step, the CD is cut so as to define a CD Card in the ISO format. In a first pre-cutting step, a breaking line is pre-cut so as to both locally weaken the CD card and separate the
25 optical data storage area, optical part, from the rest of the CD card, rest part. In a second pre-cutting step, the outline of a GSM plug is precut in the rest part. In a thinning step, the rest part is thinned from 1.2 mm to 0.8 mm, to meet the GSM requirements. In a milling step,
30 a cavity is milled inside the precut outline of the GSM plug. In an embedding step, an integrated circuit is embedded in the cavity using a glue developed specially for this purpose. In a personalization step, the

integrated circuit is electrically connected to contact pads flush with the surface of the GSM plug and graphical elements are put in the CD card.

- 5 The German patent application referenced under number DE 199 43 092 discloses a data carrier comprising an integrated circuit and an optical storage area. The data carrier is made of polycarbonate material.

10 **SUMMARY OF THE INVENTION**

It is an object of the invention to allow a reduction of the cost.

- 15 According to an aspect of the invention, a system comprising a first data carrier (MOD) and a second data carrier (CDC), the first data carrier (MOD) being removable from the second data carrier (CDC), the first data carrier (MOD) being readable by a first reading
20 machine, the second data carrier (CDC) being readable by a second reading machine, which is different than the first reading machine, is characterized in that the first data carrier (MOD) and the second data carrier (CDC) are made of two different material.

25

- The first data carrier can be, for example, a GSM plug. The second data carrier can be, for example an optical data carrier. The manufacturing of the optical data carrier and the manufacturing of the GSM plug can be
30 done independently and simultaneously using conventional material. Consequently, the invention allows a cost reduction.

These and other aspects of the invention will be described in greater detail hereinafter with reference to drawings.

5 BRIEF DESCRIPTION OF THE DRAWINGS

- Figure 1 illustrates the different steps of the manufacturing method according to the invention;
- Figure 2 illustrates the inserting step, in which a
10 low tack adhesive is used to fix the GSM plug;
- Figure 3 illustrates the use of a clipping technique to fix the GSM plug in the cavity in a removable manner;
- Figure 4 illustrates the use of a soldering technique to fix the GSM plug in the cavity in a removable manner;
- 15 - Figure 5 illustrates the use of a geometrical wedging technique to fix the GSM plug in the cavity in a removable manner;
- Figure 6 illustrates the use of a sliding technique to fix the GSM plug in the cavity in a removable manner;
- 20 - Figure 7 illustrates the use of a sliding technique to fix the GSM plug in the cavity in a removable manner;
- Figure 8 illustrates the use of a hole to facilitate the removing of the plug, for example, by finger pressure;
- 25 - Figure 9 illustrates a combination of different fixing techniques;
- Figure 10 and 11 illustrates various position of the GSM plug.

30 DETAILED DESCRIPTION

FIG. 1 illustrates the different steps of the

method according to the invention.

In a moulding step MOULD, a CD is moulded. The mould can be, for example, a master CD made of glass, in
5 which polycarbonate is injected.

In a depositing step DEP, a round-shaped metallic layer M is deposited on the moulded CD to define an optical data storage area. Advantageously, a varnish
10 protective layer can be deposited on the round-shaped metallic layer. The round-shaped metallic layer is preferably centred on the CD.

In a cutting step CUT, the moulded CD is cut in
15 the form of an ISO card CDC.

In an optional pre-cutting step PRECUT which is followed by the cutting step CUT, a breaking line BL is pre-cut so as to both locally weaken the CD card CDC and
20 separate the optical data storage area, optical part OP, from the rest of the CD card, rest part RP.

In a creating step CREAT, a cavity CAV is created in the rest part RP. To that end, milling
25 techniques can, for example, be used.

In an inserting step INSERT, an already manufactured GSM plug MOD is inserted in the cavity. The GSM plug MOD comprises a plastic body and integrated
30 circuit electrically connected to contact pads flush with the surface of the plastic body. The plastic body is, for example, modified acrylonitrile butadiene styrene (ABS), moulded ABS or polyvinylchloride (PVC). As illustrated in

fig. 2, the GSM plug MOD is fixed in the cavity CAV using a low tack adhesive LT. Thus, the GSM plug MOD can be easily removed from the cavity CAV. Contrary to the prior art, the GSM plug can be manufactured with conventional material independently and simultaneously. So the manufacturing is faster. Further when creating a GSM plug MOD in a CD card of polycarbonate, the quality is lower because polycarbonate is not easy to manufacture. In addition we have to stick the module in the polycarbonate. To that end, a specific glue has to be developed. Thus, the invention allows an enhanced quality and a cost reduction.

In a personalization step PERS graphical elements PE are put on the CD card.

The description hereinbefore illustrates the following features:

A system comprising a first data carrier (MOD) and a second data carrier (CDC), the first data carrier (MOD) being removable from the second data carrier (CDC), the first data carrier (MOD) being readable by a first reading machine, the second data carrier (CDC) being readable by a second reading machine, which is different than the first reading machine, the system being characterized in that the first data carrier (MOD) and the second data carrier (CDC) are made of two different material.

30

The description of the above mentioned embodiment illustrates rather than limits the invention. It will be evident that there are numerous alternatives,

which fall within the scope of the appended claims. In this respect, the following closing remarks are made.

5 The second data carrier can be, for example, an optical data carrier and more generally any other data carrier that is readable via a reading machine that is different than that of the first data carrier, for example, a magnetic data carrier.

10 The cutting step CUT, the pre-cutting step PRECUT, and the creating step CREAT could also be replaced by the moulding step MOULD using an appropriate mould.

15 In the inserting step INSERT, the GSM plug MOD has been inserted in the cavity CAV using a low tack adhesive LT. Other techniques can also be used to fix the GSM plug MOD in the cavity CAV.

20 As illustrated in fig. 3 to fig. 5 the GSM plug MOD can be fixed by driving in techniques, for example, as illustrated in fig. 3, clipping techniques. The clipping elements CE can be moulded in the moulding step MOULD.

25 As illustrated in fig. 4, soldering techniques can also be used. It can be, for example, hot soldering or ultrasound soldering.

 As showed by fig.5, geometrical wedging techniques can be also used. To this purpose grooves or bevelled edges can be, for example, used.

30 As illustrated in fig. 6, the GSM plug MOD can also be fixed using sliding techniques.

 As illustrated in fig. 6 a through d, the plug can be inserted in the CD card in a visible manner. As

illustrated in Fig. 6e, the plug can also be inserted in the CD card CDC in a non-visible manner.

Alternatively, as illustrated in fig. 6d and 7, one of the edges of the GSM plug MOD can touch the breaking line BL, so that the rest part RP has to be
5 break to remove the plug MOD from the cavity CAV. This technique can be used, for example, as a fraud detector.

As illustrated in Fig. 8 a hole H can be provided
10 in the cavity CAV so that the GSM plug can be easily removed from the CD card CDC, for example, by finger pressure. Instead of using a hole H for facilitating the removing of the GSM plug, a notch, pre-cut lines or a groove can also be used.

15

As illustrated in Fig. 9, combining the above-mentioned techniques (i.e. clipping, soldering geometrical wedging, sliding in techniques...) can also be used to both fix and enable the easy removing of the GSM
20 plug MOD.

As illustrated in Fig. 10a and fig. 11a, if the GSM plug is in the ISO position, a relatively small portion of the card can be used for optical storage.

25

As illustrated in Fig. 10b to 10e and in Fig. 11 b to g, there are other possibilities to position the GSM plug in such a manner that the useful optical storage area is bigger. As illustrated in Fig. 10b the GSM plus is transferred from the ISO position to the left. As
30 illustrated in Fig. 10 c, the GSM plus is translated from the ISO position to the left and rotated 180 degrees. As illustrated in Fig. 10d, the GSM plug is rotated 270 degrees from the ISO position. As illustrated in Fig. 10e

the GSM plug is rotated 90 degrees from the ISO position.
Other positions are shown in Fig. 11b to 11g.

CLAIMS

1. A system comprising a first data carrier (MOD) and
5 a second data carrier (CDC), the first data carrier
(MOD) being removable from the second data carrier
(CDC), the first data carrier (MOD) being readable
by a first reading machine, the second data carrier
(CDC) being readable by a second reading machine,
10 which is different than the first reading machine,
the system being characterized in that the first
data carrier (MOD) and the second data carrier
(CDC) are made of two different material.
- 15 2. The system according to claim 1, characterized in
that the first data carrier (MOD) is made of
plastic material and in that the second data
carrier (CDC) is made of polycarbonate.
- 20 3. The system according to claim 2, characterized in
that the first data carrier (MOD) is made of
acrylonitrile butadiene styrene.
4. The system according to claim 2, characterized in
25 that the first data carrier (MOD) is made of
polyvinylchloride.
5. The system according to claim 1, characterized in
that the first data carrier (MOD) is a GSM plug
30 (MOD) and in that the second data carrier is an
optical data carrier (CDC).
6. The system according to claim 1, characterized in

that the first data carrier (MOD) is inserted in the second data carrier (CDC) using clipping elements.

- 5 7. The system according to claim 1, characterized in that the first data carrier (CDC) is inserted in the second data carrier using sliding techniques.
- 10 8. The system according to claim 5, characterized in that one edge of the GSM plug MOD touch a breaking line of the optical data carrier (CDC).
- 15 9. A method of manufacturing a system comprising a first data carrier (MOD) and a second data carrier (CDC), the first data carrier (MOD) being removable from the second data carrier (CDC), the first data carrier (MOD) being readable by a first reading machine, the second data carrier (CDC) being readable by a second reading machine, which is different than the first reading machine, the method comprising the following steps:
- 20 - a first manufacturing step, in which the first data carrier (MOD) is manufactured using a first material;
- 25 - a second manufacturing step, in which the second data carrier (CDC) is manufactured using a second material, the second material being different from the first material; and
- 30 - an inserting step in which the first data carrier (MOD) is inserted in the second data carrier (CDC).

1/10




Fig. 1

2/10




Fig. 2

3/10




Fig. 3

4/10




Fig. 4

5/10




Fig. 5

6/10







Fig. 6a




Fig. 6c

Fig. 6d

Fig. 6e

Fig. 6b

7/10




Fig. 7




Fig. 8

8/10









Fig. 9

9/10




Fig. 10

10/10




Fig. 11

INTERNATIONAL SEARCH REPORT

Application No

T/IB 03/03146

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 G06K19/08

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 G06K

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, PAJ, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	WO 01 24169 A (EKUS BRYAN) 5 April 2001 (2001-04-05) abstract page 4, line 15 -page 5, line 21 page 7, line 26 -page 8, line 2 figures 2,4	1-9
Y	HAGHIRI, YAHYA: "Vom Plastik zur Chipkarte" 1999, HANSER VERLAG, MUNICH, VIENNA XP002254868 ISBN: 3-446-21249-3 page 26 -page 29 page 240 -page 241	1-5,9
Y	EP 0 702 325 A (NACIONAL MONEDA TIMBRE) 20 March 1996 (1996-03-20) abstract; figures 1-4	6,7
	--- -/-	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

A document member of the same patent family

Date of the actual completion of the international search

18 September 2003

Date of mailing of the international search report

08/10/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+31-70) 340-3016

Authorized officer

Koegler, L

INTERNATIONAL SEARCH REPORT

Intern

Application No

/IB 03/03146

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	EP 0 328 124 A (DEUTSCHE BUNDESPOST) 16 August 1989 (1989-08-16) column 1, line 16 -column 4, line 22; figure 2 ----	6
Y	DE 199 43 092 A (ORGA KARTENSYSTEME GMBH) 15 March 2001 (2001-03-15) cited in the application abstract; figures 1-5 ----	8
Y	PATENT ABSTRACTS OF JAPAN vol. 015, no. 203 (M-1116), 24 May 1991 (1991-05-24) -& JP 03 055296 A (TOSHIBA CORP), 11 March 1991 (1991-03-11) abstract; figures 1,3,4 -----	6,7

INTERNATIONAL SEARCH REPORT

I Application No

T/IB 03/03146

Patent document cited in search report		Publication date		Patent family member(s)	Publication date
WO 0124169	A	05-04-2001	AU	7843400 A	30-04-2001
			WO	0124169 A1	05-04-2001
EP 0702325	A	20-03-1996	ES	2102317 A2	16-07-1997
			AU	695335 B2	13-08-1998
			AU	3069995 A	04-04-1996
			CA	2158530 A1	20-03-1996
			EP	0702325 A2	20-03-1996
			FI	954418 A	20-03-1996
			NO	953678 A	20-03-1996
			NZ	280036 A	24-06-1997
			ZA	9507890 A	29-04-1996
EP 0328124	A	16-08-1989	DE	3804361 C1	29-09-1988
			DE	58909742 D1	14-11-1996
			EP	0328124 A2	16-08-1989
DE 19943092	A	15-03-2001	DE	19943092 A1	15-03-2001
			AU	7506800 A	10-04-2001
			WO	0118750 A1	15-03-2001
			EP	1129431 A1	05-09-2001
JP 03055296	A	11-03-1991	NONE		